



TimbrCORE™

FLOORganic
by KAINDL

Plank Size: 9.6" x 54.45" (244mm x 1383mm)
Thickness: 9.5mm
Pad: 1mm ECO Underlay
Core: AQUApro HDF core
Finish: Authentic Textured
Wear Rating: AC5
Waterproof: Yes
Bevel: Aqua Protect Soft Bevel
Gloss: Ultramatte
Texture: Real Grain Digital
Installation: Angle/Tap on All Grades and Levels
Res. Warranty: Limited Lifetime Residential
Com. Warranty: 5-Year Lt. Commercial




GENERAL DATA

DESCRIPTION	METHOD	RESULT	DETAILS
Class of Use	EN ISO 10874	Class 33	All Residential plus heavy commercial
Abrasion Resistance	EN15468: 2016 (Annex A)	AC5	IP ≥ 5000 cycles
Impact Resistance	EN15468: 2016 (Annex A)	Big Ball: ≥ 1000mm (29.53"), Small Ball: ≥ 15N	
Stain Resistance	EN438-2.15	Group 1 + 2: Level 5, Group 3: Level 4	
Residual Indentation	EN424	No Visible Damage Foot Type 0: 1mm /32kg	
Castor Chair Resistance	EN425 (Type W)	No Visible Damage 25,000 cycles	
Thickness Swell Test	EN 15468: 2016	PASSED	≤ 15%
NALFA Surface Swell Test	NALFA LF-01	qualitativ ≤ 2 and < 0.3mm	
Impact Sound Transmission	ASTM E492	IIC = 50 ΔIIC = 20	HUD 50
Airborne Sound Transmission Loss	ASTM E90	STC = 52	HUD 50

32% in Ambient Sound Reduction based on IHD Standard W431

ENVIRONMENTAL CERTIFICATES

Green Guard	GOLD
AFFSET	A+
CARB 2	Compliant
TSCA Title VI	Compliant
Content	No heavy metals + lead/cadmium present
Dangerous Substances	No carcinogenic, mutagenic or reprotoxic substances present (class 1A & 1B)
Plasticizer	ORTHOPHTHALATES FREE



PHONE
800-325-2625

FAX
888-505-7383

WWW.
herregan.com